


Audio-Video-Modulatoren

Audio video modulators

Audio-Video-Modulator | mono | VHF | UHF | S

Audio video modulator | mono | VHF | UHF | S

- ✓ Moduliert ein A/V-Signal in ein HF-Signal
- ✓ CCD-Überwachungskamera, Videokamera, DVD-Player etc. anschließbar
- ✓ VHF-/UHF-Kanal oder Sonderkanal zwischen K 5...12, S 11...41 und K 21...69 wählbar
- ✓ LED-Display zur Kanalanzeige
- ✓ Inkl. Steckernetzteil, Cinchkabel (RCA) und F-auf-IEC-Adapter (CFA 10-00)
- ✓ Modulates an AV Signal to a RF-Signal
- ✓ CCD camera, video camera or VCR etc. can be connected
- ✓ Free selectable VHF/UHF channel or special channel between CH 5...12, S 11...41 and CH 21...69
- ✓ LED display
- ✓ With plug-in power supply, cinch cable (RCA) and F to IEC adapter (CFA 10-00)

Artikel Article	AVM 1-02
Artikelnummer Part No.	AVM00102
Verpackungseinheit Packing unit	1
	
Frequenzbereich Frequency range	175...862 MHz
VHF Kanäle VHF channels	5...12
Sonderkanäle Special channels	S 11...41
UHF Kanäle UHF channels	21...69
Frequenzgang Flatness	±1,0 dB
Ausgangspegel Output level	70 dBµV
HF Ausgangsimpedanz RF Output impedance	75 Ohm
Video Eingangsimpedanz Video input impedance	75 Ohm
Audio Eingangsimpedanz Audio input impedance	10 kOhm
Video Eingangspegel Video input level	1 V _{SS}
Audio Eingangspegel Audio input level	1 V _{SS}
Anschlüsse HF Connectors RF	F-Buchse F female
Anschlüsse Video Connectors video	RCA/Cinch-Buchse RCA/Cinch female
Anschlüsse Audio Connectors audio	Cinch-Buchse Cinch female
Steckernetzteil Power supply	230 V~/50 Hz 6 V~/500 mA
Maße (B × H × T) ca. Dimensions (W × H × D) appr.	105 × 91 × 36 mm

